

AECOM

Introduction

- What is Green Infrastructure?
- What are the Goals of Green Infrastructure?
 - Water Quality Issues

- Planning Considerations
 - Watershed, neighborhood, site
- Examples
- Lessons Learned









What is Green Infrastructure?

"Green infrastructure uses vegetation, soils, and natural processes to manage water and create healthier urban environments. At the scale of a city or county, green infrastructure refers to the patchwork of natural areas that provides habitat, flood protection, cleaner air, and cleaner water. At the scale of a neighborhood or site, green infrastructure refers to stormwater management systems that mimic nature by soaking up and storing water."

http://water.epa.gov/infrastructure/greeninfrastructure/gi_what.cfm

Examples

- Downspout
 Disconnection
- Rainwater Harvesting
- Rain Gardens
- Planter Boxes
- Bioswales
- Permeable Pavers

- Green Alleys and Streets
- Green Parking
- Green Roofs
- Urban Tree Canopy
- Land Conservation

Benefits

- Surface water quality/ quantity
- Groundwater Recharge
- Habitat
- Air Quality
- Energy and Climate

What is Green Infrastructure?

"Green infrastructure uses <u>vegetation</u>, soils, and natural processes to manage water and create healthier urban environments. At the scale of a city or county, green infrastructure refers to the patchwork of <u>natural</u> areas that provides habitat, flood protection, cleaner air, and cleaner water. At the scale of a neighborhood or site, green infrastructure refers to <u>stormwater management systems that mimic nature by soaking up and storing water</u>."

http://water.epa.gov/infrastructure/greeninfrastructure/gi_what.cfm

Examples

- Downspout
 Disconnection
- Rainwater Harvesting
- Rain Gardens
- Planter Boxes
- Bioswales
- Permeable Pavers

- Green Alleys and Streets
- Green Parking
- Green Roofs
- Urban Tree Canopy
- Land Conservation

Benefits

- Surface water quality/ quantity
- Groundwater Recharge
- Habitat
- Air Quality
- Energy and Climate


What are the Goals of Green Infrastructure?

- Manage Small Frequent Storms


 - Water QualityWater Quantity

Not Traditional Stormwater Management Goals.

- Aesthetics, Carbon reduction, Energy Use, Air Quality
- Key differences from Traditional Stormwater Management
 - Diffuse locations
 - Water Quality
 - Volume Reduction
 - Habitat
 - More "Public" Than Traditional Infrastructure



Green Roof Applications



Pervious Infrastructure



Rain Gardens and Bioswales











FIGURE 1-4 Plots of Effective Impervious Area (EIA, or "connected imperviousness") against metrics of biologic response in fish populations. SOURCE: Reprinted, with permission, from Wang et al. (2001). Copyright 2001 by Springer.



Source: Watershed Protection Research Monographs No. 1, Impacts of Impervious Cover on Aquatic systems. March 2003. Prepared by Center for Watershed Protection 8391 Main Street Ellicott City, MD 21043.



BOX 3-7 Continued

TABLE 3-2A Dissolved Nitrate and Total Nitrogen Export Rates from Forest and Developed Land-Use Catchments in the Baltimore Ecosystem Study

Cotobosout	Landline	Nitrate (kg N/ha/yr)			Total N (kg N/ha/yr)				
Catchment	Land Use	2000	2001	2002	2000				
Pond Branch	Forest	0.11	0.08	0.04	.47	.37	0.17		
McDonogh	Agriculture	17.6	12.9	4.3	20.5	14.5	4.5		
Baisman Run	Mixed Forest and Suburban	7.2	3.8	1.5	8.2	4.2	1.7		
Dead Run	Urban	3.0	2.9	2.9	5.6	5.3	4.2		

TABLE 3-2B Dissolved Phosphate and Total Phosphorus Export Rates from Forest and Developed

Land-Use Catchments in the Baltimore Ecosystem Study

0.11		Phos	phate (kg P	/ha/yr)	Total P (kg P/ha/yr)			
Catchment	Land Use	2000	2001	2002	2000	2001	2002	
Pond Branch	Forest	0.009	0.007	0.003	0.02	0.014	0.006	
McDonogh	Agriculture	0.12	0.080	0.022	0.22	0.14	0.043	
Baisman Run	Mixed Forest and Suburban	0.009	0.005	0.002	0.02	0.011	0.004	
Dead Run	Urban	0.039	0.037	0.03	0.10	0.10	0.08	

Source: Shields, C., L.E. Band, N. Law, P. Groffman, S. Kaushal, K. Savvas, G. Fisher, K. Belt. In Press. Streamflow distribution of nonpoint source nitrogen export from urban-rural catchments in the Chesapeake Bay Watershed. Water Resources Research.

From: Urban Stormwater Management in the United States. The National Academies Press, Washington DC. October 15, 2008







BOX 3-7 Continued

TABLE 3-2A Dissolved Nitrate and Total Nitrogen Export Rates from Forest and Developed Land-Use Catchments in the Baltimore Ecosystem Study

Catalamant	Landline	Nitr	ate (kg N/ha	ı/yr)	Tot	a/yr)	
Catchment	Land Use	2000	2001	2002	2000	2001	2002
Pond Branch	Forest	0.11	0.08	0.04	.47	.37	0.17
McDonogh	Agriculture	17.6	12.9	4.3	20.5	14.5	4.5
Baisman Run	Mixed Forest and Suburban	7.2	3.8	1.5	8.2	4.2	1.7
Dead Run	Urban	3.0	2.9	2.9	5.6	5.3	4.2

TABLE 3-2B Dissolved Phosphate and Total Phosphorus Export Rates from Forest and Developed

Land-Use Catchments in the Baltimore Ecosystem Study

Catchment		Phosphate (kg P/ha/yr)			Total P (kg P/ha/yr)			
	Land Use	2000	2001	2002	2000	2002		
Pond Branch	Forest	0.009	0.007	0.003	0.02	0.014	0.006	
McDonogh	Agriculture	0.12	0.080	0.022	0.22	0.14	0.043	
Baisman Run	Mixed Forest and Suburban	0.009	0.005	0.002	0.02	0.011	0.004	
Dead Run	Urban	0.039	0.037	0.03	0.10	0.10	0.08	

Source: Shields, C., L.E. Band, N. Law, P. Groffman, S. Kaushal, K. Savvas, G. Fisher, K. Belt. In Press. Streamflow distribution of nonpoint source nitrogen export from urban-rural catchments in the Chesapeake Bay Watershed. Water Resources Research.

From: Urban Stormwater Management in the United States. The National Academies Press, Washington DC. October 15, 2008







BOX 3-7 Continued

TABLE 3-2A Dissolved Nitrate and Total Nitrogen Export Rates from Forest and Developed Land-Use Catchments in the Baltimore Ecosystem Study

Cotohmont	Landline	Nitrate (kg N/ha/yr)			Total N (kg N/ha/yr)			
Catchment	Land Use	2000	2001	2002 2000		2001		2002
Pond Branch	Forest	0.11	0.08	0.04	.47	.37	7	0.17
McDonogh	Agriculture	17.6	12.9	4.3	20.5	14.5		4.5
Baisman Run	Mixed Forest and Suburban	7.2	3.8	1.5	8.2	4.2		1.7
Dead Run	Urban	3.0	2.9	2.9	5.6	5.3		4.2

TABLE 3-2B Dissolved Phosphate and Total Phosphorus Export Rates from Forest and Developed Land-Use Catchments in the Baltimore Ecosystem Study

0-1-1	Landling	Phosphate (kg P/ha/yr)			Total P (kg P/ha/yr)			
Catchment	Land Use	2000	2001	2002	2000	2002		
Pond Branch	Forest	0.009	0.007	0.003	0.02	0.014	0.006	
McDonogh	Agriculture	0.12	0.080	0.022	0.22	0.14	0.043	
Baisman Run	Mixed Forest and Suburban	0.009	0.005	0.002	0.02	0.011	0.004	
Dead Run	Urban	0.039	0.037	0.03	0.10	0.10	0.08	

Source: Shields, C., L.E. Band, N. Law, P. Groffman, S. Kaushal, K. Savvas, G. Fisher, K. Belt. In Press. Streamflow distribution of nonpoint source nitrogen export from urban-rural catchments in the Chesapeake Bay Watershed. Water Resources Research.

From: Urban Stormwater Management in the United States. The National Academies Press, Washington DC. October 15, 2008








What do I mean by "Planning for performance"?

- There is a lot of literature about the benefits of individual types of GI...we can get percent removal efficiencies or typical outlet concentrations
- When retrofitting an area planning to meet a specific target with a specific budget can lead to optimization
- Planning allows projects to achieve water quality/ quantity goals for a larger area while optimizing cost and effectiveness
- Planning is important at each "scale"



Watershed Scale

Neighborhood Scale

Site Scale

- Goals and Targets
- Regulatory Drivers
- Public Engagement
- Budget (Capital and O&M)
- Watershed Characterization
- Prioritize Locations
- Prioritize GI Types
- Alternatives
- Implementation Period

- Verify Physical Suitability of Sites
- Collect Data
- Public Engagement
- Budget (Capital and O&M)
- Select Locations
- Select GI Types
- Develop Design and Construction Schedule

- Collect Data
 - Infiltration
 - Utilities
 - Contamination
- Cost Estimating
- Implement Design and Construction Schedule

Develop plan to meet goals within budget and other constraints

Refine projects, project locations, and costs

Engineer, design, construct, and maintain

Watershed Scale


Neighborhood Scale

Site Scale

- Source Assessment
- Potential Locations
- Feasible GI Types
- Costs

- Select Sites
- Collect Data
- Select GI Types
- Develop Design and Construction Schedule
- Public Engagement

- Collect Data
- Cost Estimating
- Design
- Construct
- Maintain




Distributed GI Stormwater Features

Prioritization/ Optimization Analysis

- Treatment Effectiveness (quality and quantity)
- Public Acceptance
- Synergy with non-priority opportunities
- Capital Cost
- O&M Cost
- Greatest treatment for least cost




Watershed Scale Example



Key


- Red = more pollutants
- Green = less pollutants

- Set target
- Analyze sources
- Identify locations and types
- Assess level of control
 - Do BMPs achieve target?



Watershed Scale Example

 Goal: To reduce bacteria loading from storm water outfalls to Village Beaches








AECOM

Watershed Scale Example



- Locations
- Size
- Treatment
- Volume
- Cost

Maximized
Treatment for
Available \$

Rain Gardens Infiltration Trench

Neighborhood Scale Example

BIORETENTION EXAMPLE


Sidewalk Planters - Linear detention or retention planters located linearly along a sidewalk in the furnishings zone.

- Required Footprint = 5% x DMA (for CSD)
- Required Footprint = 8% x DMA (for flooding)

Bulbout Planters - Both detention and retention bioretention facilities located in curb extensions or bulbouts at the downstream end of the area managed.




Proposed Flow-Through Sidewalk Planter





Proposed Bioretention Bulbout

technology footprint
drainage management area





Burnsville, MN


Residential Neighborhood

Rain Garden Retrofits

Long-Term Monitoring



BEFORE



Paired Study of Residential Street Runoff Control




Diagram courtesy of the City of Burnsville, MN from their Burnsville Stormwater Retrofit Study






Diagram courtesy of the City of Burnsville, MN from their Burnsville Stormwater Retrofit Study

17 Rain Gardens
5.3 acres treated and 7.5 acres controlled
Average treated lot < .5 acres
Average total rain gardens < 1 acre







Lessons Learned

- Cost estimating at watershed scale is challenging
- Setting targets helps drive performance
- Not all identified locations will work
- Site specific data is very important for site specific performance
- Long term costs
- Maintenance is required

Closing Thoughts

- Watershed scale planning allows for economic optimization of GI types and locations
- To achieve goals/ targets neighborhood analysis and site scale engineering and designs need to be consistent with early planning
- Constraints need to be well understood at beginning of project
- Public perception
- Opportunity to "marry" two forms of public work effort (street, sidewalks, stormwater management)






Thank You

Troy.Naperala@AECOM.com








Watershed Scale Planning

- Discuss goals, constraints, and funding with owner
 - Storm size targeted for control
 - Pollutant of concern
 - Limitations on location
 - Construction budget
- GIS Data Analysis
 - Topography,
 - Hydrography
 - Soils
 - Land use



Collect and analyze site specific data

What is Our Approach to Green Infrastructure?

- -**Designed** Holistically
- -Planned Comprehensively
- -Laid Out **Strategically**
- -Planned and Implemented **Publically**
- -Grounded in principles and practices of **Diverse Professions**